



EU-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.



Certificate N° 0075/1677/161/05/20/1595

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : Progressive Safety Footwear & Clothing Ltd
101 WORTHING ROAD SHEFFIELD S9 3JN ,UK
UK

Description

PPE Type :

a safety footwear

Product reference :

3CX/B

Article code :

Construction and material of outsole : CEMENT /TPU+ EVA+RUBBER OUTSOLE

Pictures :



Safety Footwear
MODEL 3CX/B
UK8 EUR42



EN ISO 20345:2011 S3 WR SRA
Order No. 000000 DOM 12/2019
Progressive Safety Footwear Ltd
An Official Licensee of JCB
101, Worthing Rd, Sheffield S9 3JN, UK
MADE IN CHINA

Reference standard : EN ISO 20345 : 2011

Classification : I

Category : S3 WR SRA

Size range : 40-46

Slip resistance : SRA

Toecap nature : Non Metallic

Insert nature : Non Metallic

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from MAY 2020

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by

Date of first issue : 26 May 2020

Didier GUISADO

End of validity date : 26 May 2025

Certification and Quality Manager



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir: Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

Progressive Safety Footwear & Clothing Ltd

MANUFACTURER'S TECHNICAL FILE

Reference of the product : 3CX/B

Article code :

Technical file index : 01

Last update : MAY 2020

IDENTIFICATION

Reference of the product : 3CX/B
Article Code :
Basic model
Technical file index : 01
Last update : MAY 2020

Manufacturer :

Progressive Safety Footwear & Clothing Ltd
101 WORTHING ROAD SHEFFIELD S9 3JN ,UK
UK

tel : 0114-270-2430
fax : 0114-270-2406

Factory :

Liyuen Footwear manufacturing Co., Ltd
No.9#,Industrial Road, Nantou Town,ZhongShan,Guangdong,China
China

Tel : 0760-23122558
Fax : 0760-23122598

Regence Footwear (Cambodia) Co Ltd
On Doung Village, Baek Chan District Ang Snuol Commune, Kandal Province
Cambodia

Tel : 012-237389
Fax : N/A

FOOTWEAR DESCRIPTION

Footwear description:

The classification of this footwear is: I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear
The design of this footwear is: B : ankle boot

Visual description:

General view :



Outsole view :



Reference of the mould : 06710

Range of sizes :

40-46

Construction and material of outsole :

CEMENT /TPU+ EVA+RUBBER OUTSOLE

Field of use

Toy industry, construction site , mine for mechanical risks

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§1.4	Manufacturer's instructions and information is available	☒	☐	Standard
			☒	Instruction for use
			☐	Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	☒	☒	Standard
			☒	Instruction for use
			☐	Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§2.6	PPE is intended for use in potentially explosive atmospheres	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	☒	☒	Standard
			☒	Instruction for use
			☐	Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§2.14	Multi-risk PPE	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§3.1.1	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒	Standard
			☒	Instruction for use
			☒	Marking

FOOTWEAR CONSTITUTION

	Ref	Material	Color
UPPER	LY-EMFG-01	EMBOSSSED FULL GRAIN COW LEATHER	BLACK
	LY-RB-01	SCRATCHING TEXTURE RUBBER PIECE(TOE PUFF)	BLACK
	LY-MTL-02	METAL HOOK & RING	DK.SILVER
COLLAR	LY02	PU	BLACK
TONGUE	LY-SUEDE01	COW SUEDE LEATHER	BLACK
VAMP LINING	LY06+	MESH(LY06)+WATERPROOF FILM	BLACK
QUARTER LINING	LY06+	MESH(LY06)+WATERPROOF FILM	BLACK
	LY06	TONGUE/COLLAR LINING : MESH	BLACK
INSOCK	LY-INSK-69	MESH+EVA,REMOVABLE	BLACK/DK.GREY
OUTSOLE	06710	TPU(SEAT REGION)+EVA(3 LAYERS ON SEAT REGION AREA AND 2 LAYERS ON OTHER AREA)+ RUBBER	BLACK/WHITE
INSOLE	LY06+,TSO	BLACK MESH(LY06)+WATERPROOF FILM+NON-METALLIC ANTI- PENETRATION	BLACK/WHITE/BLUE
TOE CAP	887 NM	887 COMPOSITE TOECAP	WHITE
INSERT	TSO	NON-METALLIC ANTI-PENETRATION	WHITE/BLUE
DECORATIVE ELEMENTS		JCB LOGO (TONGUE&SEAT REGION)	YELLOW/BLACK/WHITE
		BACKING OF EYELET STAY : PU	BLACK

PROTECTION SCOPE

Basic requirements :

This product has been designed to be a safety footwear.

The technical rules are :

European Standard EN ISO 20344 : 2011 Personal protective equipment - test methods for footwear

European Standard EN ISO 20345 : 2011 : Personal protective equipment - Safety footwear

It is a category II product

Requirement of the standard EN ISO 20345 : 2011 concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution (SRA)

Requirement of the paragraph 5.8.1. Design of the standard EN ISO 20345 : 2011 concerning cleated outsole.

At the date of certificate, the product is in compliance with Annex XVII of European REACH regulation (n° 1907/2006 and revisions)

Additional requirements :

The additional requirements are :

- Closed seat region
- Antistatic footwear
- Energy absorption of seat region
- Fuel oil resistance
- Upper : Water penetration and water absorption
- Penetration resistance
- Water resistance (through test or machine method)

MARKING - PACKAGING

Information printed on the footwear :

- * Logo of the authorized representative
- * Logo **CE**
- * Manufacturer's type designation
- * Postal address of manufacturer
- * Footwear's reference 3CX/B
- * Article code
- * Size
- * Year of manufacture and at least quarter
- * The number and year of the Standard used
- * The symbol(s) of the additional requirements

Marking example :



The location of marking is : TONGUE LINING

Method of marking on the footwear :

Stitching in the back of tongue

Packaging :

1 pair/box,5pairs/carton

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	References	Laboratory	References
CTC	D161015439_2	CTC	D191019788_1
CTC	D180815029_1	CTC	D191122185_1
CTC	D180815031_2	CTC	D191225677_1
CTC	D180815506_2	CTC	D200201592_1
CTC	D180918130_1	CTC	D200302019_1
CTC	D181121178_1	Intertek	GZHT90784728
CTC	D181122651_1	Intertek	GZHT90838990
CTC	D190100373_1	Intertek	GZHT90945865
CTC	D190610728_1	Intertek	GZHT90948490
CTC	D190918122_1	Intertek	GZHT90953536

MEANS OF CONTROL

1.To control the quality of raw materials follow the methods below:

We asked our suppliers to test their upper leather for Cr VI, PH and DMFu by themselves; asked lining suppliers to check tear strength, especially abrasion resistance; and the suppliers for toecaps and insert need to test impact/compression and penetration resistance for their components...after all raw material can reach relevant requirement, we will accept them and use in mass production.

2. During development, we will take some samples to check the main physical properties, such as impact, compression, slip resistance and so forth, in order that we can control the quality from development and will avoid some additional troubles in the following steps; if the result can meet requirement, we will process forward; otherwise we need pay more attention to development for the better shoes;

3. We control the whole procedure from cutting to package. Every step, relevant QC will check the quality, the semi-finished goods and finished shoes will be discarded if cannot reach requirement of quality. Of course we take some samples from line to test bond strength, impact ect to confirm the mass production are under control. Finally, before shipment, the QC will perform the final inspection randomly, the shoes will be delivered in case the result is acceptable.

4.When do bulk the production each batch, we shall pick up some shoes from producing site randomly to test impact, compression, penetration, leather CR VI.... to control the quality to match the requirment of standard EN ISO 20345:2011.”

PPE subject to ageing :

Peremption period : 3 years when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available with product.